

SAFETY DATA SHEET

ULTIMEG 2000/372 CLEAR

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME ULTIMEG 2000/372 CLEAR
 PRODUCT NO. U372C
 SUPPLIER AEV PLC
 MARION STREET
 BIRKENHEAD
 MERSEYSIDE CH41 6LT
 +44(0)151 647 3322
 +44(0)151 647 3377

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
XYLENE	215-535-7	1330-20-7	50-70%	R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

Flammable. Irritating to skin. Harmful by inhalation and in contact with skin.

CLASSIFICATION Xn;R20/21. Xi;R38. R10.

4 FIRST-AID MEASURES

GENERAL INFORMATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INHALATION

Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. If breathing stops, provide artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

DO NOT INDUCE VOMITING! Remove victim immediately from source of exposure. Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention immediately!

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

SPECIFIC HAZARDS

Fire creates: Toxic gases/vapours/fumes of Carbon. Carbon dioxide (CO₂). Carbon monoxide (CO). Nitrous gases (NO_x). Hydrocarbons.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Clean-up personnel should use respiratory and/or liquid contact protection. Absorb in vermiculite, dry sand or earth and place into containers.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Use explosion proof electric equipment.

ULTIMEG 2000/372 CLEAR

STORAGE PRECAUTIONS

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a cool, dry well-ventilated place. Keep in original container.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

INGREDIENT COMMENTS

OES = Occupational Exposure Standard.

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Well-ventilated area.

RESPIRATORY EQUIPMENT

Respiratory protection must be used if air contamination exceeds acceptable level.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Use approved safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Light brown		
ODOUR	Organic solvents.		
SOLUBILITY	Insoluble in water		
BOILING POINT (°C)	138 - - 142 760 mm Hg	RELATIVE DENSITY	0.97 23
VAPOUR DENSITY (air=1)	3.7	VAPOUR PRESSURE	0.93 kPa 20
VISCOSITY	4.7 Ps 25	FLASH POINT (°C)	27 CC (Closed cup).
AUTO IGNITION TEMPERATURE (°C)	490	FLAMMABILITY LIMIT - LOWER(%)	1
FLAMMABILITY LIMIT - UPPER(%)	6.6		

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat. Avoid contact with oxidisers or reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION

INHALATION

Harmful by inhalation. Vapours may cause headache, fatigue, dizziness and nausea.

INGESTION

Harmful if swallowed. May cause internal injury.

SKIN CONTACT

May cause sensitisation by skin contact. May be absorbed through the skin. Product has a defatting effect on skin.

EYE CONTACT

Irritation of eyes and mucous membranes.

ULTIMEG 2000/372 CLEAR

HEALTH WARNINGS

INHALATION. Gas or vapour is harmful on prolonged exposure or in high concentration. **SKIN CONTACT.** Irritating to skin. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. **EYE CONTACT.** Irritating to eyes. **INGESTION.** May cause stomach pain or vomiting.

ROUTE OF ENTRY

Inhalation. Skin absorption.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Dangerous for the environment if discharged into watercourses.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



PROPER SHIPPING NAME

PAINT or PAINT RELATED MATERIAL

UN NO. ROAD	1263	ADR CLASS	Class 3: Flammable liquids.
UN NO. SEA	1263	IMDG CLASS	3.3
IMDG PACK GR.	III	MARINE POLLUTANT	Yes.



UN NO. AIR	1263	ICAO CLASS	3
AIR PACK GR.	III		

15 REGULATORY INFORMATION

LABELLING



Harmful

CONTAINS

XYLENE

RISK PHRASES

R10	Flammable.
R38	Irritating to skin.
R20/21	Harmful by inhalation and in contact with skin.

SAFETY PHRASES

S24	Avoid contact with skin.
S51	Use only in well-ventilated areas.
S36/37	Wear suitable protective clothing and gloves.
S60	This material and its container must be disposed of as hazardous waste.

UK REGULATORY REFERENCES

Petroleum (Consolidation) Act, as amended 1984 SI 1244. Highly Flammable Liquid Regulations 1972.

ENVIRONMENTAL LISTING

Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980.

REVISION DATE: 13/05/2005

ULTIMEG 2000/372 CLEAR

EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EEC.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16 OTHER INFORMATION

REVISION DATE 13/05/2005

REV. NO./REPL. SDS GENERATED 9

SDS NO. 1

RISK PHRASES IN FULL

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.

R38 Irritating to skin.